

UT216A 600A True RMS Digital Clamp Meter



Specifications	Range	UT216A
AC current (A)	600A	$\pm(2.5\%+5)$
AC current frequency response		50-60Hz
AC voltage (V)	750V	$\pm(1.2\%+5)$
AC voltage frequency response		40~400Hz
DC voltage (V)	1000V	$\pm(0.8\%+1)$
Resistance (Ω)	60M Ω	$\pm(1\%+2)$
Capacitance (F)	60mF	$\pm(4\%+5)$
Features		
Display count		6000
Auto range		√
Jaw opening		30mm
True RMS		√
Diode	Around 3.0V	√
NCV		√
Data hold		√
Relative mode		√
MAX/MIN		√
LCD backlight		√
Flashlight		√
Auto power off		√

Continuity buzzer		√
Low battery indication	≤3.6V	√
Input protection		√
Input impedance for DCV	≥10MΩ	√
General Characteristics		
Power	1.5V battery (R03) x 3	
Display	38mm x 24mm	
Product color	Red and grey	
Product net weight	280g	
Product size	220mm x 75mm x 40mm	
Standard accessories	Batteries, test leads	
Standard individual packing	Gift box, carrying bag, English manual	
Standard quantity per carton	40pcs	
Standard carton measurement	485mm x 345mm x 385mm	
Standard carton gross weight	20.6kg	